# ShengYingTech Suzhou CHINA

### MATERIAL SAFETY DATA SHEET

## SECTION I - PRODUCT IDENTIFICATION

TRADE NAME: MicroC Foam PH series HMIS RATING: H-0, F-1, R-0

Micro cellular polyurethane / polyethylene terephthalate

CAS NUMBER: Polyurethane: 9009-54-5

Polyethylene terephthalate: 25038-59-9

CHEMICAL FAMILY: Urethane Polymer EMERGENCY PHONE: 86-512-6689 0180

#### <u>SECTION II – HAZARDOUS INGREDIENTS</u>

No hazardous materials present as defined in OSHA's Hazard Communication Standard 29 CFR 1910, 1200.

Composition/Information on ingredients				
Component Name	Chemical Name	wt%(in component)	CAS No.	
Foam	Polyurethane	85~90	9009-54-5	
	Aluminum hydroxide	5~10	21645-51-2	
	Carbon black	1	1333-86-4	
Film	Polyethylene terephthalate	>99	25038-59-9	

This form is provided as a reference to our customers.

#### <u>SECTION III - PHYSICAL DATA</u>

BOILING POINT: NA SPECIFIC GRAVITY: 0.36 – 0.44

VAPOR PRESSURE: NA EVAPORATION RATE: NA

SOLUBILITY IN WATER: Negligible pH: NA

APPERANCE: Solid Foam ODOR: Slight Odor

#### <u>SECTION IV – FIRE AND EXPLOSION HAZARD DATA</u>

FLASH POINT : NA FLAMMABLE LIMITS : <u>NA</u> Lel <u>NA</u> Uel

ShengYingTech
Suzhou China

<b>Cellular Urethanes</b>	
Outland Orothianoc	

## ShengYingTech Suzhou CHINA

	MET	HOD	USED	:	NA
--	-----	-----	------	---	----

EXTINGUISHING MEDIA : X Water Fog X Foam X CO<sub>2</sub>
X Dry Chemical Other

SPECIAL FIRE FIGHTING Decomposition in a fire may produce toxic fumes.

PROCEDURES: Fire fighters should be equipped with self-contained

breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARDS :

polyurethane materials may generate dense smoke in a fire.

HAZARDOUS DECOMPOSITION

PRODUCTS:

CO, CO<sub>2</sub>, oxides of nitrogen, HCN, and traces of

incompletely burned carbon compounds.

AUTOIGNITION TEMPERATURE :

NΑ

#### SECTION V - HEALTH HAZARD DATA

**EFFECTS OF** 

OVEREXPOSURE: None are expected with normal handling. Cutting and other

finishing operations may create polyurethane dust. Ventilation and personal protection should be similar to all operations

generating nuisance dust.

**FIRST AID PROCEDURES** 

INHALATION: Remove to fresh air and seek medical attention if necessary. EYE CONTACT: Flush eyes with water and seek medical attention if necessary.

SKIN CONTACT: Wash thoroughly with soap and water.

INGESTION: NA

SECTION VI - REACTIVITY DATA

STABILITY: X Stable Unstable

CONDITIONS TO AVOID: NA

INCOMPATIBILITY: NA

(MATERIALS TO AVOID)

HAZARDOUS POLYMERIZATION : \_\_\_May Occur \_\_\_X\_Does Not Occur

HAZARDOUS DECOMPOSITION: See Section IV.

#### <u>SECTION VII – SPECIAL PROTECTION INFORMATION</u>

RESPIRATORY PROTECTION: None required with normal handling.

ShengYingTech
Suzhou China

## ShengYingTech **Suzhou CHINA**

**VENTILATION:** 

Recommended in cutting/finishing operations or hot wire cutting LOCAL EXHAUST:

operations.

MECHANICAL(GENERAL): Recommended as with all industrial operations.

**EYE PROTECTION:** Safety glasses are recommended in all industrial operations.

PROTECTIVE CLOTHING: Leather gloves to avoid skin contact as a precautionary

measure.

OTHER: NA

## <u>SECTION VIII – ENVIROMENTAL DATA</u>

**ENVIROMENTAL TOXICITY DATA: NA** 

WASTE DISPOSAL METHOD: Landfill in accordance with all local, state, and federal

regulations.

CONTAINER DISPOSAL: Landfill in accordance with all federal, state, and local

regulations.

This product contains the following toxic chemicals subject to the reporting requirements of 313 of the Emergency Planning and Community Right-To-Know ACT of 1986 and 40CFR 372:

CAS# CHEMICAL NAME PERCENT BY WEIGHT

None NA NA

#### <u>SECTION IX – SHIPPING DATA</u>

**DOT SHIPPING NAME:** NA

DOT HAZARD CLASSIFICATION: NA

UN/NA CODE: NA

### SECTION X - SPILL OR LEAK PROCEDURES

**RESPONSE TO SPILLS:** Clean-up avoiding creation of nuisance dust.

**REPORTABLE QUANTITY:** NA

ShengYingTech

**Suzhou China** 

Cellular Urethanes	

# ShengYingTech Suzhou CHINA

## <u>SECTION XI - SPECIAL PRECAUTIONS</u>

RECOMMENDED STORAGE

PRACTICE AND CONDITIONS: Cool dry area.

OTHER PRECAUTIONS: Hot wire cutting operations should be exhausted to prevent

exposure to irritating vapors.

NA = Not Applicable NE = Not Established

DATE PREPARED: Nov18, 2016 PREPARED BY: ShengYingTech

APPROVED BY: ShengYingTech

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULT TO BE OBTAINED FORM THE USE THEREOF.

SHENGYHINGTECH ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS, OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISK ASSOCIATED WITH THE USE OF THE MATERIAL.

